

## MATERIAL SAFETY DATA SHEET

Westmoreland Advanced Materials, LLC  
210 C Schreiber Industrial Park  
Arnold, PA 15068

Emergency Telephone: 724-339-2040  
Prepared By: Technology Dept.  
Telephone 724-339-2041

**SECTION I: Product Identification and Use**

Product Name: WAM™ CG/AL 60 LC

Product Identification No.: Not Applicable

NFPA/WHMIS Rating: 2-0-0

Product Use: Castable Refractory

Formula: Not Applicable

Chemical Name/Synonym: Not Applicable

Chemical Family: Not Applicable

**SECTION II: Hazardous Ingredients**

Hazardous Ingredients	%	CAS No.	TLV TWA (mg/m <sup>3</sup> )*	LD <sub>50</sub>	LC <sub>50</sub>
Crystalline Silica	13 - 32	Not Applicable	Not applicable	Not Applicable	Not Applicable
Above includes: Quartz		14464-46-1	0.05	Not Applicable	Not Applicable
Cristobalite		15468-32-3	0.05	Not Applicable	Not Applicable
Tridymite		14808-60-7	0.1	Not Applicable	Not Applicable
Calcium Aluminate Cement	1 - 10	12042-68-1	10 total / 3 respirable	Not Applicable	Not Applicable

\* Source: American Conference of Governmental Industrial Hygienists (ACGIH); TL V-TWA for Crystalline Silica are for the respirable fraction of particulate matter.

SARA Title III Section 313 Toxic Chemicals: None

Calcium Aluminate Cement is a low health risk by inhalation and should be treated as a nuisance dust.

**SECTION III: Physical Data**

Appearance and Odor: Granular Mixture, White to

Freezing Point (°C): Not Applicable

Gray Color, Earthy Odor

pH (10% Solids): 8-10

Physical State: Solid

Vapor Density (Air=1): Not Applicable

Percent Volatile by Volume: 0

Solubility in Water: Slight

Odor Threshold: Not Available

Vapor Pressure (mmHg): Not Applicable

Boiling Point (°C): Not Applicable

Coefficient of Oil/Water Dist: Not Available

Specific Gravity (g/cc): 1.5

Evaporation Rate: Not Applicable

**SECTION IV: Fire and Explosion Hazard Data**

Flammability: Product is non-flammable and will not support combustion.

Upper Flammable Limit (o/v): Not Applicable

Means of Extinction: Not Applicable

Explosion Sensitivity to Impact: Not Applicable

Auto-Ignition Temperature (°C): Not Applicable

Lower Flammable Limit (o/v): Not Applicable

Flashpoint (°C) and Method: Not Applicable

Explosion Sensitivity to Static Discharge: Not Applicable

Hazardous Combustion Products: Not Applicable

**SECTION V. Reactivity Data**

Stability: Stable

Hazardous Polymerization: Will Not Occur

Hazardous Decomposition Products: None

Reactivity: Hydraulic Setting

Incompatibility: Concentrated Acids

**SECTION VI: Health Hazard/Toxicological Data**Route of Entry:

Skin Contact: Yes

Inhalation: Yes

Skin Absorption: No

Ingestion: Yes

Eye Contact: Yes

Effects of Acute Exposure to Product:

Skin: May irritate skin.

Eye: May irritate and/or abrade eyes.

Inhalation: Congestion of the throat, nasal passages, and upper respiratory system.

Ingestion: Unknown.

Effects of Chronic Exposure to Product:

Skin: None Known

Eye: None Known

Inhalation: According to the International Agency for Research on Cancer (IARC), there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources.

Ingestion: Unknown.

Exposure Limits: See Section II

Teratogenicity: None Known

Reproductive Toxicity: None Known

Mutagenicity: None Known

Irritancy of Product: Moderate irritation may occur.

Sensitization to the Product: None Known

Synergistic Materials: None Known

Carcinogenicity: Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group I IARC).

California Proposition 65: This product contains crystalline silica, a chemical known to the state of California to cause cancer.

SECTION VII: Preventive Measures, and Spill or Leak Procedures

Personal Protective Equipment:

Gloves: Protective Gloves

Eye: Goggles or Safety Glasses with Side Shield

Clothing: Long Sleeved and Legged

Respirator: NIOSH Approved Respirator

Footwear: Safety Shoes (Not Essential)

Other: None Known

Engineering Controls: General mechanical ventilation is normally adequate.

Leak and Spill Procedure: Dry material may be swept, shoveled, or vacuumed up. Return clean, dry material to original container, or dispose. Place wet material in a container for disposal.

Waste Disposal: The tearout and disposal of this product may generate dust. During tearout, observe the exposure limits outlined in Section II, and the personal protection precautions in Section VII. Dispose in accordance with Federal, State and Local regulations.

Handling Procedures: Follow good housekeeping and hygienic practices.

Storage Requirements: Store in a dry place.

Special Shipping Information: Not regulated by USA DOT, Canadian TDB Class, and PIN.

SECTION VIII: First Aid Measures

Skin: Wash with soap and water. If irritation occurs, seek medical attention.

Eyes: Flush with clean water for 15 minutes. Seek medical attention.

Inhalation: Remove to dust free area and fresh air. If continuing respiratory distress, seek medical attention.

Ingestion: Seek medical attention immediately. Unless instructed by physician, do not induce vomiting. Product is non-toxic as supplied, but its abrasive nature may damage internal organs.

SECTION IX: Other Information

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein; however, Westmoreland Advanced Materials, LLC. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.